










قیمت محصولات برگزیده 2023 Akuvox					
	Product Image	Product nr	Description	Price	Product Link
Door phone		Akuvox X915 Smart Intercom	High-end Smart Door Phone 1.Size: 350x130x53.9mm (HxWxD) 2.Body material: 316 grade stainless steel 3.RAM / ROM: 2GB / 16GB 4.Display: 8" IPS LCD 5.Screen: 8" capacitive touch screen 6.Camera: 2MP camera,star light 7.Relay In/Out: 3/3 8.Card reader: 13.56MHz & 125kHz 9.RS485 & Weigand port 10.IR Sensor 11.Installation: In-wall 12.Water-proof & Dust-proof: IP65 13. IK10 14. Onvif	2,200\$	اینتر کام Akuvox مدل X915
		Akuvox X912 Smart Intercom	Vandal-resistant Door Phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Weigand port 8.linux 9.Installation: Wall-mounted 10.Water-proof & Dust-proof:IP65	1300\$	اینتر کام Akuvox مدل X912
		Akuvox R29CL smart intercom	SIP Android Door Phone with Facial LTE module 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	1,800\$	اینتر کام Akuvox مدل R29C-L
		Akuvox R29CB smart intercom	SIP Android Door Phone with Facial Recognition & mask & temperture measurement 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	2,750\$	اینتر کام Akuvox مدل R29C-B





	<p>Akuvox R29CT smart intercom</p>	<p>SIP Android Door Phone with Facial Recognition & FingerPriting 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)</p>	<p>1,807\$</p>	<p>اینتر کام Akuvox مدل R29C-T</p>
	<p>Akuvox R29C Smart Intercom</p>	<p>SIP Android Door Phone with Facial Auxiliary Camera 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)</p>	<p>1,650\$</p>	<p>اینتر کام Akuvox مدل R29C</p>
	<p>Akuvox R29S Smart Intercom</p>	<p>SIP Android Door Phone with Facial Standard version 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)</p>	<p>1,336\$</p>	<p>اینتر کام Akuvox مدل R29S</p>





	<p>Akuvox R28A IP Video Intercom</p>	<p>SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 4.3 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall</p>	<p>755\$</p>	<p>اینتر کام مدل R28A Akuvox</p>
	<p>Akuvox R27A IP Video Intercom</p>	<p>SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Wide-angle camera: 116° (H), 60° (V) 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall</p>	<p>495\$</p>	<p>اینتر کام مدل R27A Akuvox</p>
	<p>R20K in-Wall</p>	<p>Palm-size Door phone 1.Front panel : Aluminum alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120° 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: In-wall 9.Linux 10.Onvif 11.Wiegand & RS485 port: Support 12.Card reader: 13.56MHz & 125kHz</p>	<p>418\$</p>	<p>اینتر کام مدل R20K Akuvox</p>
	<p>R20K on-Wall</p>	<p>Palm-size Door phone 1.Front panel : Aluminum alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120° 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: on-wall 9.Linux 10.Onvif 11.Wiegand & RS485 port: Support 12.Card reader: 13.56MHz & 125kHz</p>	<p>385\$</p>	<p>اینتر کام مدل R20K Akuvox</p>

	<p>Akuvox R20B5X in -wall</p>	<p>1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 5 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Flush-mounted DIM: 226x108x52mm18. Onvif</p>	<p>385\$</p>	<p>اینتر کام مدل R20B-5</p>
	<p>Akuvox R20B5X on-wall</p>	<p>Multi-botton Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 5 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: On-wall</p>	<p>352\$</p>	<p>اینتر کام مدل R20B-5</p>
	<p>Akuvox R20B4X in-wall</p>	<p>Multi-botton Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 4 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif</p>	<p>374\$</p>	<p>اینتر کام مدل R20B-4</p>






	<p>Akuvox R20B4X on-wall</p>	<p>Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 4 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: On-wall 17. Onvif</p>	<p>341\$</p>	<p>اینتر کام آکುವوکس مدل R20b-4</p>
	<p>Akuvox R20B3X in-wall</p>	<p>Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 3 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall</p>	<p>363\$</p>	<p>اینتر کام آکுவوکس مدل R20B-3</p>
	<p>Akuvox R20B3X on-wall</p>	<p>Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 3 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: On-wall 17. Onvif</p>	<p>330\$</p>	<p>اینتر کام آکுவوکس مدل R20B-3</p>


	<p>Akuvox R20B2X in-wall</p>	<p>Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 2 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif</p>	<p>341\$</p>	<p>اینتر کام آکುವوکس مدل R20B-2</p>
	<p>Akuvox R20B2X on-wall</p>	<p>Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 2 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7. Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: On-wall 17. Onvif</p>	<p>308\$</p>	<p>اینتر کام آکுவوکس مدل R20B-2</p>
	<p>Akuvox R20A In-Wall</p>	<p>single-button SIP video door phone 1. Linux 2. Body material: Aluminum 3. Camera: 3M pixels, automatic lighting, Wide-angle camera: 116° 4. RF Card Reader 13.56MHZ&125KHZ Card reader 5. Output Relay: 2 output relays for door opener 6. Water-proof & Dust-proof: IP65 7. Installation: In-wall 8. POE or 12V DC Connector (if not using PoE) 9. Wiegand & RS485 port: Support 10. Complies with SIP standard for easy integration in every SIP PBX; 11. Onvif</p>	<p>300\$</p>	<p>اینتر کام آکுவوکس مدل R20A</p>





	<p>Akuvox R20A On-Wall</p>	<p>single-button SIP video door phone 1.Linux 2.Body material: Aluminum 3.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116° 4.RF Card Reader 13.56MHZ&125KHZ Card reader 5.Output Relay: 2 output relays for door opener 6.Water-proof & Dust-proof: IP65 7.Installation:On-wall 8.POE or 12V DC Connector (if not using PoE) 9.Wiegand & RS485 port:Support 10.Complies with SIP standard for easy integration in every SIP PBX; 11. Onvif</p>	<p>267\$</p>	<p>اینتر کام Akuvox مدل R20A</p>
	<p>Akuvox SIP Intercom-R20A- 2wire in-wall</p>	<p>Linux single-button SIP video door phone 1.Body material: Alluminum 2.Camera: 2M pixels, automatic lighting,Wide-angle camera: 120°3.RF Card Reader 13.56MHZ&125KHZ Card reader 4.Output Relay: 1 output relays for door opener 5.Water-proof & Dust-proof: IP65 6.Installation: on-wall 7.Onvif 8.Power supply : 48VDC two-wire power supply 9.Complies with SIP standard for easy integration in every SIP PBX;</p>	<p>327\$</p>	
	<p>Akuvox SIP Intercom-R20A- 2wire on-wall</p>	<p>single-button SIP video door phone 1.Linux 2.Body material: Aluminum 3.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116° 4.RF Card Reader 13.56MHZ&125KHZ Card reader 5.Output Relay: 2 output relays for door opener 6.Water-proof & Dust-proof: IP65 7.Installation:On-wall 8.POE or 12V DC Connector (if not using PoE) 9.Wiegand & RS485 port:Support 10.Complies with SIP standard for easy integration in every SIP PBX; 11. Onvif</p>	<p>297\$</p>	
	<p>Akuvox SIP Intercom-E12W</p>	<p>Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: in-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz,NFC,Bluetooth and WIFI 7.micro SD Card Slot: 1 8.Onvif 9.Wiegand & RS485 port:Support 10. Water-proof & Dust-proof: IP65</p>	<p>172\$</p>	



	<p>Akuvox SIP Intercom-E12S</p>	<p>Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: in-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz,NFC,Bluetooth 7.micro SD Card Slot: 1 8.Onvif 9.Wiegand & RS485 port:Support 10. Water-proof & Dust-proof: IP65</p>	<p>155\$</p>	<p>اینتر کام Akuvox مدل E12S</p>
	<p>Akuvox SIP Intercom-E11</p>	<p>Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz 7.Onvif 8.Wiegand & RS485 port:Support</p>	<p>204\$</p>	<p>اینتر کام Akuvox مدل E11R</p>
	<p>Akuvox SIP touch PanelC319A (SIP SERVER Enabled)</p>	<p>SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3.Bluetooth,wifi, Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. .Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE)</p>	<p>550\$</p>	<p>مانیتور Akuvox مدل C319A</p>
	<p>Akuvox SIP Touch Panel X933W</p>	<p>SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. Bluetooth,wifi 7. body material: plastic 8.IO: 8 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE)</p>	<p>440\$</p>	<p>مانیتور Akuvox مدل X933W</p>



Indoor Monitor

	<p>Akuvox SIP Touch Panel X933S</p>	<p>SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. body material: plastic 7.RS485 port: Support 8.Relays out: 2 9.Installation: Wall-mounted & Desktop 10.IO:8</p>	<p>408\$</p>	<p>مانیتور Akuvox مدل X933S</p>
	<p>Akuvox SIP Touch Panel X933S In-wall</p>	<p>SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. body material: plastic 7.RS485 port: Support 8.Relays out: 2 9. IO:8</p>	<p>508\$</p>	<p>مانیتور Akuvox مدل X933S</p>
	<p>Akuvox SIP Touch Panel IT83R (SIP SERVER Enabled)</p>	<p>Android SIP Indoor 1.front panel: Aluminum 2.10" capacitive touch screen with energy saving mode 3.Reception of a HD picture from the door communicator 4.Two-way communication based on SIP v2.0 protocol 5.POE or 12V DC Connector (if not using PoE) 6 Supports US or European electrical wall box mounting 7.Tamper resistant design8.Desktop Stand (optional) 8.Memory Slot: 1 micro SD 9.RS485 port: Support 8.Relays out: 2 9.IO:8 10.Installation: Wall-mounted & Desktop</p>	<p>535\$</p>	<p>مانیتور Akuvox مدل IT83R</p>
	<p>Akuvox SIP Touch Panel IT83A (SIP SERVER Enabled)</p>	<p>Android SIP Indoor Wifi and Bluetooth & Camera: 1M pixels 1.front panel: Aluminum 2.10" capacitive touch screen with energy saving mode 3.Reception of a HD picture from the door communicator 4.Two-way communication based on SIP v2.0 protocol 5.POE or 12V DC Connector (if not using PoE) 6 Supports US or European electrical wall box mounting 7.Tamper resistant design8.Desktop Stand (optional) 8.Memory Slot: 1 micro SD 9.RS485 port: Support 8.Relays out: 2 9.IO:8 10.Installation: Wall-mounted & Desktop</p>	<p>613\$</p>	<p>مانیتور Akuvox مدل IT83A</p>
	<p>Akuvox SIP Touch Panel C319S (SIP SERVER Enabled)</p>	<p>Android SIP Indoor 1.front panel: plastic 2.10" capacitive touch screen with energy saving mode 3.Reception of a HD picture from the door communicator 4.Two-way communication based on SIP v2.0 protocol 5.POE or 12V DC Connector (if not using PoE) 6 Supports US or European electrical wall box mounting 7.Tamper resistant design8.Desktop Stand (optional) 8.Memory Slot: 1 micro SD 9.RS485 port: Support 8.Relays out: 2 9.IO:8 10.Installation: Wall-mounted & Desktop</p>	<p>472\$</p>	<p>مانیتور Akuvox مدل C319S</p>

	<p>Akuvox SIP Touch Panel C319W (SIP SERVER Enabled)</p>	<p>Android SIP Indoor 1. front panel: plastic 2. 10" capacitive touch screen with energy saving mode 3. Reception of a HD picture from the door communicator 4. Two-way communication based on SIP v2.0 protocol 5. POE or 12V DC Connector (if not using PoE) 6. Supports US or European electrical wall box mounting 7. Tamper resistant design 8. Desktop Stand (optional) 9. Memory Slot: 1 micro SD 10. RS485 port: Support 11. Relays out: 2 12. IO: 8 13. wifi, bluetooth 14. Installation: Wall-mounted & Desktop</p>	<p>500\$</p>	<p>ماینیتور مدل C319W Akuvox</p>
---	--	---	--------------	--

	<p>Akuvox SIP touch Panel- C315W</p>	<p>Android SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. WIFI Enabled , Bluetooth 7. front panel: plastic 8. RS485 port: Support 9. Relays out: 1 10. IO: 8</p>	<p>297\$</p>	<p>ماینیتور مدل C315W Akuvox</p>
	<p>Akuvox SIP touch Panel- C315S</p>	<p>Android SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. front panel: plastic 7. RS485 port: Support 8. Relays out: 1 9. IO: 8</p>	<p>267\$</p>	<p>ماینیتور مدل C315S Akuvox</p>
	<p>Akuvox SIP touch Panel C313W-2wire</p>	<p>Linux SIP Indoor 1. 2-wire ports: 2 pair 2. 7" capacitive touch screen with energy saving mode 3. Reception of a HD picture from the door communicator 4. Two-way communication based on SIP v2.0 protocol 5. 48V DC connector (if not using NS-2) 6. Supports US or European electrical wall box mounting 7. front panel: plastic 8. RS485 port: Support 9. Relays out: 1 10. IO: 8 11. Installation: Wall-mounted & Desktop</p>	<p>198\$</p>	
	<p>Akuvox SIP touch Panel- C313S</p>	<p>Linux SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. front panel: plastic 7. RS485 port: Support 8. Relays out: 1 9. IO: 8 10. Installation: Wall-mounted & Desktop</p>	<p>143\$</p>	<p>ماینیتور مدل C313S Akuvox</p>

	<p>Akuvox SIP touch Panel-C313N</p>	<p>Linux SIP Indoor 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. with one LAN port 7. I/O port not available 8. not Relay 9.front panel: plastic 10.Installation: Wall-mounted & Desktop</p>	<p>132\$</p>	<p>ماینیتور مدل C313N Akuvox</p>
	<p>VP-R49G</p>	<p>SIP based Android Video phone 1. 7" touch screen with 1024 x 600 resolution 2. Android 9.0 OS 3. Premium audio and video quality 4. DTMF for remote door opening 5. Camera:2MP with privacy shutter 6. Built-in Bluetooth, USB, and Wi-Fi 7. Support 3rd-party apps 8. Support 2 Sip Account 9. RJ9 Handset 10. POE 11.Support Call Waiting, Call Forward, Call Transfer 12. Call on Hold, Mute, Auto-answer, Redial, DND 13.Local 3-Way Conference</p>	<p>550\$</p>	<p>تلفن تصویری مدل R49G Akuvox</p>
	<p>SP-R63G</p>	<p>Gigabit Ethernet IP Phone 1.Dual-port Gigabit Ethernet, PoE 2.Up to 6 SIP Accounts 3. 2.8" 320 *240 pixel color display with backlight 4. Support Call Waiting, Call Forward, Call Transfer 5. Call on Hold, Mute, Auto-answer, Redial, DND 6. Local 3-Way Conference 7. Phonebook (500 entries), Blacklist (100 entries),Call logs (100 entries) 8. 5 Remote Phone Book URL Supported 9. 39 Keys (with 4 Soft Keys, 10 Programmable keys)</p>	<p>175\$</p>	<p>تلفن تحت شبکه مدل SPR63G Akuvox</p>

	<p>NS-2</p>	<p>2-Wire IP network switch 1.Support network and power supply for R20A-2 or C313W-2 through 2-wire cable; 2.Support multi-level cascade through 2-wire cable; 3.Connects up to 6 pcs of Akuvox 2-wire IP intercom devices; 4.Super long transmission distance via 2-wire cable; 5.Powered by 48VDC or 24VDC power supply unit; 6.Rail mounting installation; 7.2-wire ports: 6 8.Status Indicator: 4 9.RJ45 port: 1</p>	<p>210\$</p>	<p>سوییچ شبکه مدل NS-2 Akuvox</p>
	<p>EcMSR</p>	<p>1.High performance 32bit CPU processor 2.Standard 10/100M TCP/IP communication 3.Big capacity flash chip, 120,000 card holders and 200,000 records 4.Each panel support 32 outputs and can connect a expansion panel to reach 64 outputs 5.One RS485 port for connecting expansion panel 7.Supports emergency door release input to realize fire alarm linkage or elevator's normal usage if emergency 8.Supports 1 Wiegand reader with Wiegand 26/34 protocol 9.Support working with Akuvox intercom devices by HTTP mode</p>	<p>730\$</p>	

*نکات تکمیلی:

- ✓ تمامی مدل‌های سری W دارای بلوتوث و Wifi هستند.
- ✓ مدل‌های سری A علاوه بر بلوتوث و Wifi، دارای دوربین نیز می‌باشند.
- ✓ ورژن اندروید مدل‌های هوشمند 9 Android می‌باشد.
- ✓ مدل C313 سری S, N و W با سیستم عامل Linux قابلیت اتصال به سیستم خانه هوشمند و نرم‌افزارهای اندروید را ندارند.
- ✓ آیفون‌های in-wall دارای باکس توکار با توجه به اندازه آیفون برای نصب هستند.

GeniusHome.co