

Akubela ٢٠٢٤ قيمت محصولات					
	Product Image	Product nr	Description	Price	Product Link
Smart home		SmartPanel (C319H)	Smartpanel Pro (Android Version ٩) ١,١٠" capacitive touch screen with energy saving mode ٢.zigbee ٣. body material: plastic ٤.Bluetooth,wifi, Camera ٥.Powered by PoE or external source ٦. Supports US or European electrical wall box mounting ٧. Reception of a HD picture from the door communicator ٨. IO: ٨ ٩.Two-way communication based on SIP v٢,٠ protocol ١٠.RS٤٨٥ port: Support ١١.Relays out: ٢ ١٢.Installation: Wall-mounted & Desktop ١٣.POE or ١٢V DC Connector (if not using PoE)	٦٥٠\$	مانيتور Akuvox مدل C٣١٩H
		SmartPanel (X93TH)	SmartPanel (X93TH) ١,٧" capacitive touch screen with energy saving mode ٢.zigbee ٣. body material: plastic ٤.Bluetooth,wifi ٥.Powered by PoE or external source ٦. Supports US or European electrical wall box mounting ٧. Reception of a HD picture from the door communicator ٨. IO: ٨ ٩.Two-way communication based on SIP v٢,٠ protocol ١٠.RS٤٨٥ port: Support ١١.Relays out: ٢ ١٢.Installation: Wall-mounted & Desktop ١٣.POE or ١٢V DC Connector (if not using PoE)	٥٤٠\$	مانيتور Akuvox مدل X٩٣٣H
		HyPanel Supreme (PHX1-ST)	١,١٢,٣٥" capacitive touch screen with energy saving mode ٢.zigbee ٣. body material: Metal ٤.Bluetooth ٥,wifi ٥.Dual microphone and Dual Speakers ٦. Kinds of sensors built-in. ٧. ٦ gang relays ٨. ٨ channels digital input ٩.Screen Resolution: ٢٠٠٠*١٢٠٠ pixels ١٠.RS٤٨٥ port: Support ١٢.Installation: Wall-mounted ١٣.Power Supply: ١٢~٢٤V DC ١٤.Android ١٢ ١٥.camera : ٥megapixel	٩٠٠\$	هوم سن رت Akubela مدل Hypanel Supreme
		HyPanel Supreme (PHX1-ST-KNX)	١,١٢,٣٥" capacitive touch screen with energy saving mode ٢.zigbee ٣. body material: Metal ٤.Bluetooth ٥,wifi ٥.Dual microphone and Dual Speakers ٦. Kinds of sensors built-in. ٧. ٦ gang relays ٨. ٨ channels digital input ٩.Screen Resolution: ٢٠٠٠*١٢٠٠ pixels ١٠.RS٤٨٥ port: Support ١٢.Installation: Wall-mounted ١٣.Power Supply: ١٢~٢٤V DC ١٤.Android ١٢ ١٥.camera : ٥megapixel ١٦.KNX Support	١٠٠٠\$	هوم سن رت Akubela مدل Hypanel Supreme KNX


		HyPanel Ultra (PHA1)	١. ١٠,٣٦" capacitive touch screen with energy saving mode ٢. zigbee ٣. body material: Metal ٤. Bluetooth و wifi ٥. Dual microphone and Dual Speakers ٦. Kinds of sensors built-in. ٧. ٦ gang relays ٨. A channels digital input ٩. Screen Resolution: ٢٠٠*١٢٠٠ pixels ١٠. RS٤٨٥ port: Support ١٢. Installation: Wall-mounted ١٣. Power Supply: ١٢~٢٤V DC ١٤. Android ١٢ ١٥. camera : ٥megapixel	٧٥٠\$	هوم سن رت Akubela مدل Hypanel Ultra
		HyPanel Ultra (PHA1-KNX)	١. ١٠,٣٦" capacitive touch screen with energy saving mode ٢. zigbee ٣. body material: Metal ٤. Bluetooth و wifi ٥. Dual microphone and Dual Speakers ٦. Kinds of sensors built-in. ٧. ٦ gang relays ٨. A channels digital input ٩. Screen Resolution: ٢٠٠*١٢٠٠ pixels ١٠. RS٤٨٥ port: Support ١٢. Installation: Wall-mounted ١٣. Power Supply: ١٢~٢٤V DC ١٤. Android ١٢ ١٥. camera : ٥megapixel ١٦. KNX support	٨٥٠\$	هوم سن رت Akubela مدل Hypanel Ultra KNX
		Hypanel Pro N (PGV1-N-KNX)	١. Power supply: ٢٢٠Vac ٢. Operation System: Android ١٠, ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١xRJ٤٥ ٥. ZigBee ٣, ٦. Relays out: ٢-gang ٧. Material: fireproof PC ٨. Screen: ٨" multi-touch screen ٩. Screen Resolution: ١٢٠٠x٨٠٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٣٠°C ~ +٧٠°C ١٤. Installation: Wall flush mounting ١٥. Infrared remote control: Support ١٦. Sensors Built in: Proximity sensor , Light Sensor, Temperature Sensor , Humidity Sensor ١٧. KNX Support	٧٣٠\$	هوم سن رت Akubela مدل Hypanel Pro -KNX
		Hypanel Pro N (PGV1-N)	١. Power supply: ٢٢٠Vac ٢. Operation System: Android ١٠, ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١xRJ٤٥ ٥. ZigBee ٣, ٦. Relays out: ٢-gang ٧. Material: fireproof PC ٨. Screen: ٨" multi-touch screen ٩. Screen Resolution: ١٢٠٠x٨٠٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٣٠°C ~ +٧٠°C ١٤. Installation: Wall flush mounting ١٥. Infrared remote control: Support ١٦. Sensors Built in: Proximity sensor , Light Sensor, Temperature Sensor , Humidity Sensor	٦٣٠\$	هوم سن رت Akubela مدل Hypanel Pro

		Hypanel Pro (PGV1)	١. Power supply: ٢٢٠ Vac ٢. Operation System: Android ١٠٫٠ ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١x RJ٤٥ ٥. ZigBee ٣٫٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٨" multi-touch screen ٩. Screen Resolution: ١٢٠٠ x ٨٠٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٣٠°C ~ +٧٠°C ١٤. Installation: Wall flush mounting ١٥. Infrared remote control: Support ١٦. Camera: ٥MP ١٧. Sensors Built in: Proximity sensor , Light Sensor, Temperature Sensor , Humidity Sensor	٦٥٠\$	هوم سن رت Akubela مدل Hypanel Pro
		Hypanel Pro (PGV1-KNX)	١. Power supply: ٢٢٠ Vac ٢. Operation System: Android ١٠٫٠ ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١x RJ٤٥ ٥. ZigBee ٣٫٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٨" multi-touch screen ٩. Screen Resolution: ١٢٠٠ x ٨٠٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٣٠°C ~ +٧٠°C ١٤. Installation: Wall flush mounting ١٥. Infrared remote control: Support ١٦. Camera: ٥MP ١٧. Sensors Built in: Proximity sensor , Light Sensor, Temperature Sensor , Humidity Sensor ١٨. KNX support	٧٥٠\$	
		Hypanel Lux piano (RT11)	١. Power supply: ٢٢٠ Vac ٢. Operation System: Android ١٠٫٠ ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١x RJ٤٥ ٥. ZigBee ٣٫٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٤" multi-touch screen ٩. Screen Resolution: ٤٨٠ x ٤٨٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٢٠°C ~ +٦٥°C ١٤. Installation: Wall flush mounting	٩٠٠\$	هوم سن رت Akubela مدل Hypanel lux
		Hypanel Lux Ring (CT11)	١. Power supply: ٢٢٠ Vac ٢. Operation System: Android ١٠٫٠ ٣. Ethernet ports: ١x RJ٤٥ ٤. ZigBee ٣٫٠ ٥. Material: fireproof PC ٦. Screen: ٤" multi-touch screen ٧. Screen Resolution: ٤٨٠ x ٤٨٠ pixels ٨. Environment: For indoor use only ٩. Working Humidity: ١٠~٩٠٪ ١٠. Working Temperature: -١٠°C ~ +٥٥°C ١١. Storage Temperature: -٢٠°C ~ +٦٥°C ١٢. Installation: Wall flush mounting	٨٥٠\$	هوم سن رت Akubela مدل Hypanel lux Ring – CT11

		Hypanel (PS01)	١. Power supply: ٢٢٠ Vac ٢. Operation System: Android ١٠.٠ ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١xRJ45 ٥. ZigBee ٣.٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٤" multi-touch screen ٩. Screen Resolution: ٤٨٠x٤٨٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٢٠°C ~ +٦٥°C ١٤. Installation: Wall flush mounting	٣٠. \$	هوم سن رت Akubela مدل Hypanel
		Hypanel (PS01-KNX)	١. Power supply: ٢٢٠ Vac ٢. Operation System: Android ١٠.٠ ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١xRJ45 ٥. ZigBee ٣.٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٤" multi-touch screen ٩. Screen Resolution: ٤٨٠x٤٨٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٢٠°C ~ +٦٥°C ١٤. Installation: Wall flush mounting ١٥. KNX Support	٣٦. \$	هوم سن رت Akubela مدل Hypanel
		Hypanel Lite (KS11)	١. Power supply: ٢٢٠ Vac ٢. ٤ key ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١xRJ45 ٥. ZigBee ٣.٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٣.٢V" touch screen ٩. Screen Resolution: ٣٢٠x٤٨٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٢٠°C ~ +٦٥°C ١٤. Installation: Wall flush mounting	١٩. \$	هوم سن رت Akubela مدل Hypanel lite
		Hypanel Lite (KS11-KNX)	١. Power supply: ٢٢٠ Vac ٢. ٤ key ٣. Wi-Fi, Bluetooth ٤. Ethernet ports: ١xRJ45 ٥. ZigBee ٣.٠ ٦. Relays out: Y-gang ٧. Material: fireproof PC ٨. Screen: ٣.٢V" touch screen ٩. Screen Resolution: ٣٢٠x٤٨٠ pixels ١٠. Environment: For indoor use only ١١. Working Humidity: ١٠~٩٠٪ ١٢. Working Temperature: -١٠°C ~ +٥٥°C ١٣. Storage Temperature: -٢٠°C ~ +٦٥°C ١٤. Installation: Wall flush mounting ١٥. KNX Support	٢٥. \$	هوم سن رت Akubela مدل Hypanel lite-KNX

	Smart Gas Sensor	Zigbee 3.0 protocol Transmission Frequency: 2.4 GHz Working Voltage: 12-15 V DC Standby Current: 100 mA Operating Environment: -10°C ~ +50°C Alarm LEL: 1% LEL ±3% Alarm Sound Pressure: 70 db (1 m) Installation Method: Wall-mounting or ceiling-mounting Detected Gas: Natural gas Dimensions: 80mm*29,7 mm	55\$	سنسور تشخیص نشت گاز Akubela
	Smart flood sensor	Zigbee 3.0 protocol Transmission Frequency: 2.4 GHz Working Voltage: 3 V DC Working temperature: -10°C ~ +50°C Battery Life: 1 Year Detection Method: Water Sensor probe Water proof level: IP67 Dimensions: 50 mm*18 mm	35\$	سنسور تشخیص نشت آب Akubela
	Smart Smoke Sensor	Zigbee 3.0 protocol Transmission Frequency: 2.4 GHz Working Voltage: 3 V DC Working temperature: -10°C ~ +50°C Battery Life: 1 Year Alarm Sound Pressure: more than 80 dB (3 m) Detection Method: Water Sensor probe Battery Lifespan: 3 years Dimensions: 90 mm*37 mm	55\$	سنسور تشخیص دود Akubela
	Smart Emergency Button	Zigbee 3.0 protocol Transmission Frequency: 2.4 GHz Working Voltage: 3 V DC Working temperature: -10°C ~ +50°C Battery Life: 1 Year Dimensions: 50 mm*17 mm	35\$	دکمه اعلان وضعیت اضطراری Akubela
	Smart Temperature and Humidity Sensor	Zigbee 3.0 protocol Transmission Frequency: 2.4 GHz Working Voltage: 3 V DC Working temperature: -10°C ~ +50°C Battery Life: 1 Year Dimensions: 71,7mm*23 mm	50\$	سنسور تشخیص دما و رطوبت Akubela

	Smart Motion Sensor	Zigbee 3.0 protocol Transmission Frequency: 2.4 GHz Working Voltage: 3 V DC Working temperature: -10°C ~ +55°C Detection Radius: 4m Detection Angle: 90 degree Installation Height: 2.2 m Dimensions: 48.5 mm*53.5 mm	45\$	سنسور تشخیص حرکت Akubela
	2 Gang Zigbee Switch Module	Zigbee 3.0 protocol Operation Frequency: 2.4 GHz Working Voltage: 100-240 V AC Operation temperature: -10°C ~ +55°C Operation Range: Less than 200 m IP rating: IP20 Dimensions: 47*47*18 mm Certificates: CE ROHS	55\$	ماژول دوگانه آکابلا Akubela
	1 Gang Zigbee Switch Module	Zigbee 3.0 protocol Operation Frequency: 2.4 GHz Working Voltage: 100-240 V AC Operation temperature: -10°C ~ +55°C Operation Range: Less than 200 m IP rating: IP20 Dimensions: 47*47*18 mm Certificates: CE ROHS	45\$	ماژول تک کانال آکابلا Akubela
	Smart Plug	Working voltage: 90-250 VAC 50/60 Hz Battery life: One and a half years Input current: ≤16A Output current: ≤16A Networking: Zigbee Wireless networking distance: ≥70m (in the open area) ; ≥10m (Separated by a wall) Working environment: -10°C ~ +55°C Working humidity: ≤95%RH Body size: 52.7*52.7*44mm Product size: 51*51*45mm	30\$	پریز هوشمند آکابلا Akubela
	IR Controller (IR21)	Power Supply: Micro-USB DC 5V 1A Networking Method: ZigBee 3.0 Wireless Distance: ≤70m (open environment) Infrared Frequency: 38KHz Infrared Signal Coverage: Horizontal 360°, vertical 180° (hemisphere range), 10-15m LED Indicator light: Support Buzzer: ≤50dB Infrared learning: Support Temperature Sensor: ±1°C, range: -10°C~+55°C Humidity Sensor: ±5%, range: 10%-90%RH, without condensation Material: PC+Infrared transmission material Working Temperature: -10°C ~ +55°C Working Humidity: 10%-90%RH Product Size: 68 * 48mm	50\$	کنترلر فایر آکابلا Akubela

		1Gang Swich Black & White Glass	۱. Neutral package ۲. black And Withe glass ۳. Neutral and Live Wire ۴. Tuya Zigbee	۴۵\$	کلید تک پل هوشمند Akubela
		2Gang Swich Black & White Glass	۱. Neutral package ۲. black And Withe glass ۳. Neutral and Live Wire ۴. Tuya Zigbee	۴۷\$	کلید دو پل هوشمند Akubela
		3Gang Swich Black & White Glass	۱. Neutral package ۲. NO Frame/ White & Black Glass ۳. Neutral and Live Wire ۴. Tuya Zigbee	۴۹\$	کلید سه پل هوشمند Akubela
		4Gang Swich Black & White Glass	۱. Neutral package ۲. NO Frame/ White & Black Glass ۳. Neutral and Live Wire ۴. Tuya Zigbee	۵۱\$	کلید چهار پل هوشمند Akubela
		bac-001 akubela Zigbee Thermostat	Template:BAC-001EW Sensor:NTC Precision: $\pm 0.5^{\circ}\text{C}$ Diet: 110-240 Vac / 50-60 hz Fan relay Nominal amperage: 5A; Inductive: 2A Valve relay Ampere Resistance: 2A; Inductive: 1A Temperature range: 5-30 $^{\circ}\text{C}$ Energy consumption: <1.5 W Installation: 116X116mm or European 60mm round box Timing error: <1 % Material: PC + ABS Electric charge: 2A for the valve 5A for the fan Ambient temperature: -10 $^{\circ}\text{C}$ ~ 40 $^{\circ}\text{C}$, 5% ~ 95% RH non-condensing Modbus Fan: T Speed	78\$	ترموستات هوشمند zigbee برند bac
		Smart Door and Window Sensor zigbee	۱. zigbee ۲. Input voltage: TV DC ۳. Working temperature: -10 ~ +50 C ۴. Working humidity: max 95%RH ۵. alarm triggering distance: 12+0 mm ۶. battery life: 20 times per day (more than one year)	۴۰\$	سنسور درب و پنجره