

قیمت محصولات Akuvox | نیمه اول 2026

	Product Image	Product Name	Description	Price
Door Phone		Akuvox S539 Smart Intercom & installation kit	Industry-first Metaverse Android Door Phone 1.Size: 367.5x183x35.5mm 2.Front Panel: Aluminum 3.Display: 10 Inch IPS LCD 4.Main Camera: 5M pixels, with starlight 5.Light Sensor: Support 6.Motion Sensor: Support 7.ToF Sensor: Support 8.Wiegand Port: Support 9.RS485 Port: Support 10.Line Out: Support 11.RF Card Reader: 13.56MHz & 125kHz 12.Relays Out: 3 13.Inputs: 3 14.Reset Button: 1 15.IP & IK Level: IP66 & IK08 16.Onvif	2464\$
		Akuvox S535 Smart Intercom & installation kit	Sinch Facial Recognition Door Phone 1. H.264 video and G.722 audio codec 2. Display: 5" IPS LCD capacitive touch screen 1280x720 4. Camera: 2 Mega pixels, WDR 5. Protection Level: IP66/IK08 6. PoE+ (IEEE802.3at, Power-over-Ethernet) 7.Support Wiegand, RS485, 13.56MHZ&125KHZ Card reader 8.Complies with SIP standard for easy integration in every SIP PBX 9. Installation: support Surface Mount and Flush Mount by using different bracket or box	896\$
		Akuvox S535 Smart Intercom & installation kit	Sinch Facial Recognition Door Phone 1. H.264 video and G.722 audio codec 2. Display: 5" IPS LCD capacitive touch screen 1280x720 4. Camera: 2 Mega pixels, WDR 5. Protection Level: IP66/IK08 6. PoE+ (IEEE802.3at, Power-over-Ethernet) 7.Support Wiegand, RS485, 13.56MHZ&125KHZ Card reader 8.Complies with SIP standard for easy integration in every SIP PBX 9. Installation: support Surface Mount and Flush Mount by using different bracket or box	1221\$
		Akuvox X915 Smart Intercom & installation kit	High-end Smart Door Phone 1.Size: 350x130x53.9mm (HxWxD) 2.Body material: 316 grade stainless steel 3.RAM / ROM: 2GB / 16GB 4.Display: 8" IPS LCD 5.Screen: 8" capacitive touch screen 6.Camera: 2MP camera,star light 7.Relay In/Out: 3/3 8.Card reader: 13.56MHz & 125kHz 9.RS485 & Wiegand port 10.IR Sensor 11.Installation: In-wall 12.Water-proof & Dust-proof: IP65 13. IK10 14. Onvif	2464\$
		Akuvox X912 Smart Intercom + installation kit	Vandal-resistant Door Phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Wiegand port 8.linux 9.Installation: in wall 10.Water-proof & Dust-proof:IP65 11.IK10	1456\$ + 90\$
		Akuvox X912K Smart Intercom + installation kit	Vandal-resistant Door Phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Wiegand port 8.linux 9.Installation: in wall 10.Water-proof & Dust-proof:IP65 11.IK08 12.Numeric keypad with extra buttons	1120\$ + 90\$

		Akuvox R29CL Smart Intercom & installation kit	SIP Android Door Phone with Facial LTE module 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second SMP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.PoE or 12V DC Connector (if not using PoE)	2106\$
		Akuvox R29CB smart intercom & installation kit	SIP Android Door Phone with Facial Recognition&mask&temperure muserment 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second SMP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.PoE or 12V DC Connector (if not using PoE)	3080\$
		Akuvox R29CT smart intercom & installation kit	SIP Android Door Phone with Facial Recognition&FingerPriting 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second SMP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.PoE or 12V DC Connector (if not using PoE)	2024\$
		Akuvox R29C Smart Intercom & installation kit	SIP Android Door Phone with Facial Auxiliary Camera 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second SMP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.PoE or 12V DC Connector (if not using PoE)	1848\$
		Akuvox R29S Smart Intercom & installation kit	SIP Android Door Phone with Facial Standard version 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second SMP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.PoE or 12V DC Connector (if not using PoE)	1496\$
		Akuvox E16 Smart Intercom + installation kit	budget-friendly face recognition door phone 1.Linux 2. Display: 5 Inch IPS LCD, 1280x720 3. Camera: 2M pixels, WDR 4.Wiegand & RS485 Port: Support 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. 802.3af Power-over-Ethernet 9. POE Or 12V DC Connector (if not using PoE) 10.Tamper: Support 11 Installation: Wall-mounted 12. Water-proof & Dust-proof:IP65 13. NFC & Bluetooth	700\$ + 90\$
		Akuvox E18 Smart Intercom + installation kit	budget-friendly face recognition door phone 1.Linux 2.Housing Material: Plastic 3.Display: 7 Inch IPS LCD, 1024x600 4.Camera: 2M pixels, WDR 5.Wiegand & RS485 Port: Support 6.Relay In / Out: 3 / 2 7.Bluetooth: Support 8.POE Or 12V DC Connector (if not using PoE) 9.Tamper: Support 10.Installation: Wall-mounted 11.Water-proof & Dust-proof:IP65 12.RF Card Reader: 13.56MHz,125kHz & NFC 13.Linux	902\$ + 90\$

		Akuvox R28A IP Video Intercom	SIP Intercom with Keypad 1.Front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 4.3 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall	846\$
		Akuvox S532 ST & installation kit	SIP Intercom with Keypad 1.Front panel material: Aluminium 2.Output Relay: 2 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 2.8 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall 12.IK08 & IP66 13.RFID/NFC/Bluetooth	739\$
		Akuvox S532 IP VERSION & installation kit	SIP Intercom with Keypad 1.Front panel material: Aluminium 2.Output Relay: 2 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 2.8 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall 12.IK08 & IP66 13.RFID/NFC/Bluetooth	706\$
		Akuvox R27A IP Video Intercom	SIP Intercom with Keypad 1.Front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Wide-angle camera: 116° (H), 60° (V) 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand & RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall	
		Akuvox R20K + installation kit	Palm-size Door phone 1.Front panel : Aluminum alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120° 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: on-wall 9.Linux 10.Onvif 11.Wiegand & RS485 port: Support 12.Card reader: 13.56MHz & 125kHz	431\$ + 37\$
		Akuvox R20K - Black + installation kit	Palm-size Door phone 1.Front panel : Aluminum alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120° 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: on-wall 9.Linux 10.Onvif 11.Wiegand & RS485 port: Support 12.Card reader: 13.56MHz & 125kHz	431\$ + 37\$
		Akuvox R20B5X + installation kit	1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 5 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Flush-mounted DIM: 226x108x52mm 18. Onvif	394\$ + 37\$

		Akuvox R20B4X + installation kit	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 4 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif	382\$ + 37\$
		Akuvox R20B3X + installation kit	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 3 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation:in-wall 17. Onvif	370\$ + 37\$
		Akuvox R20B2X + installation kit	Multi-button Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 2 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif	345\$ + 37\$
		Akuvox x910	1. Front panel: Aluminum 2. Single speed-dial button with blue backlight; 3. Wide-angle of main camera: 150° (H), 116° (V), 5M pixels 4. Auxiliary Camera: 2M pixels, automatic lighting 5. Package Detection & QR Code Scanning 6. Complies with SIP & ONVIF 7. IK08& IP66	840\$
		Akuvox R20A + installation kit	single-button SIP video door phone 1.Linux 2.Body material: Aluminum 3.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116° 4.RF Card Reader 13.56MHZ&125KHZ Card reader 5.Output Relay: 2 output relays for door opener 6.Water-proof & Dust-proof: IP65 7.Installation:On-wall 8.POE or 12V DC Connector (if not using PoE) 9.Wiegand & RS485 port:Support 10.Complies with SIP standard for easy integration in every SIP PBX; 11. Onvif	299\$ + 37\$
		Akuvox R20A-2-wire + installation kit	Linux single-button SIP video door phone 1.Body material: Alluminum 2.Camera: 2M pixels, automatic lighting,Wide-angle camera: 120°3.RF Card Reader 13.56MHZ&125KHZ Card reader 4.Output Relay: 1 output relays for door opener 5.Water-proof & Dust-proof: IP65 6.Installation: on-wall 7. Onvif 8.Power supply : 48VDC two-wire power supply 9.Complies with SIP standard for easy integration in every SIP PBX;	366\$ + 37\$
		Akuvox R25A + installation kit	Linux Single speed-dial button with blue backlight 1.Body material: Alluminum 2.Camera:4M pixels, automatic lighting 3.RF card reader: 13.56MHz & 125kHz, NFC 4. Relays out: 2 5. IP Rating: IP65 6. Installation: Flush-mounted or Wall-mounted 7.Onvif 8. 802.3af Power-over-Ethernet 9.Wide-angle camera: 150° (H), 150° (V)	366\$ + 37\$
		Akuvox E13S & installation kit	Linux single-button SIP video door phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Wiegand port 8.POE or 12V DC Connector (if not using PoE) 8.POE or 12V 9.Installation: in wall-on wall 10.Water-proof & Dust-proof: IP65	179\$

		Akuvox SIP Intercom-E12W	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz,NFC,Bluetooth and WIFI 7.micro SD Card Slot: 1 8.Onvif 9.Wiegand & RS485 port:Support 10. Water-proof & Dust-proof: IP65	193\$
		Akuvox E12S SIP Intercom	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz,NFC,Bluetooth 7.micro SD Card Slot: 1 8.Onvif 9.Wiegand & RS485 port:Support 10. Water-proof & Dust-proof: IP65	174\$
		Akuvox DB01 SIP Intercom	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 1 output relays for door opener 4.Installation: on-wall 5.: 1 call buttonInfrared 6.Onvif 7.Wiegand & RS485 port:Support 8. Water-proof & Dust-proof: IP65 9.power supply: 12V 2A	129\$
		Akuvox E11 SIP Intercom + Installation Kit	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95° angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz 7.Onvif 8.Wiegand & RS485 port:Support	228\$ + 37\$
		Akuvox E20S SIP Intercom	Linux single-button SIP intercom 1.Body material: Aluminium 2.Output Relay: 2 output relays for door opener 3.Installation: on-wall 4.Infrared sensor 5.1 call button,Infrared Sensor 6.Wiegand & RS485 port:Support	280\$
indoor monito		Akuvox x937 SIP touch Panel	Smart AI Monitor 1. 15.4" touch screen with 1920 x 1080 resolution 2. Android 14 3. Support Ethernet & WiFi6 4. Powered by PoE+ or external source 5. Support HDMI input and CCTV system integration 6. Built-in AI voice assistant 7. On-wall or desktop mounting options available	1344\$
		Akuvox S567W SIP touch Panel	A smart intercom, as well as a gear for audiophile 1.1280*800 2.Android 12 3.Front panel: Plastic 4.RAM / ROM: 4GB /16 GB 5.Display: 10 Inch IPS LCD 6.Screen: 10 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 2 9.Bell in: 1 10.Alarm Input : 8 11. Wifi 12.Bluetooth	661\$
		Akuvox S567 SIP touch Panel	A smart intercom, as well as a gear for audiophile 1.1280*800 2.Android 12 3.Front panel: Plastic 4.RAM / ROM: 2GB /8 GB 5.Display: 10 Inch IPS LCD 6.Screen: 10 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 2 9.Bell in: 1 10.Alarm Input : 8	627\$
		Akuvox S565 SIP touch Panel	1.resolution 1024*600 2.Linux 3.Front panel: Plastic 4.RAM / ROM: 128MB /128MB 5.Display: 10 Inch TFT LCD 6.Screen: 10 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 1 9.Bell in: 1 10.Alarm Input : 8	358\$
		Akuvox S563W SIP touch Panel	Android SIP Indoor 1.8" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6.WIFI Enabled, Bluetooth 7.front panel: plastic 8.RS485 port: Support 9.Relays out: 1 10.IO:8 11.Android 12	366\$

		Akuvox S563 SIP touch Panel	Android SIP Indoor 1. 8" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6.front panel: plastic 7.RS485 port: Support 8.Relays out: 1 9.IO:8 10.Android 12	333\$
		Akuvox S562W SIP touch Panel	1.resolution 1024*600 2.Linux 3.Front panel: Plastic 4.RAM / ROM: 128MB /128MB 5.Display: 7 Inch TFT LCD 6.Screen: 7 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 1 9.Bell In: 1 10.Alarm Input : 8 11.Wifi & bluetooth	215\$
		Akuvox S562 SIP touch Panel	1.resolution 1024*600 2.Linux 3.Front panel: Plastic 4.RAM / ROM: 128MB /128MB 5.Display: 7 Inch TFT LCD 6.Screen: 7 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 1 9.Bell In: 1 10.Alarm Input : 8	181\$
		Akuvox IT88A SIP touch Panel	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: Aluminium alloy 3. Bluetooth,wifi, Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE port: 1 Port	728\$
		Akuvox IT88S SIP touch Panel	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: Aluminium allo. 3.Powered by PoE or external source 4.Supports US or European electrical wall box mounting 5. Reception of a HD picture from the door communicator 6. IO: 8 7.Two-way communication based on SIP v2.0 protocol 8.RS485 port: Support 9.Relays out: 2 10.Installation: Wall-mounted & Desktop 11.POE or 12V DC Connector (if not using PoE) 12. PoE port: 1 Port	728\$ + 90\$
		Akuvox C319A SIP touch Panel (SIP SERVER Enabled)	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3. Bluetooth,wifi, Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE port: 1 port	616\$
		Akuvox C319W SIP touch Panel (SIP SERVER Enabled)	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3. Bluetooth,wifi 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE Port: 1 port	582\$
		Akuvox SIP touch Panel-C319S (SIP SERVER Enabled)	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3. Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE Port: 1 port	549\$

	Akuvox SIP Touch Panel X933W	SIP Indoor unit (Android Version 9) 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. Bluetooth, wifi 7. body material: plastic 8. IO: 8 9. RS485 port: Support 10. Relays out: 2 11. Installation: Wall-mounted & Desktop 12. POE or 12V DC Connector (if not using PoE)	493\$
	Akuvox X933W SIP Touch Panel In-wall	SIP Indoor unit (Android Version 9) 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. Bluetooth, wifi 7. body material: plastic 8. IO: 8 9. RS485 port: Support 10. Relays out: 2 11. POE or 12V DC Connector (if not using PoE)	493\$
	Akuvox X933S SIP Touch Panel & Installation kit	SIP Indoor unit (Android Version 9) 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. body material: plastic 7. RS485 port: Support 8. Relays out: 2 9. Installation: Wall-mounted & Desktop 10. IO: 8	457\$
	Akuvox X933S SIP Touch Panel In-wall & Installation kit	SIP Indoor unit (Android Version 9) 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. body material: plastic 7. RS485 port: Support 8. Relays out: 2 9. IO: 8	569\$
	Akuvox C316W SIP touch Panel	Front panel: Plastic OS : Android 12 RAM / ROM: 2GB / 8GB Display: 7 Inch TFT LCD Screen: 7 Inch capacitive touch screen RS485 port: Support Relay out: 1 Bell in: 1 I/O: 8 Microphone: -58dB Speaker: 4Ω / 2W Ethernet ports: 2xRJ45, 10/100Mbps adaptive 802.3af Power-over-Ethernet 12V DC connector (if not using PoE) Installation: Wall-mounted & Desktop Dimension: 200.2x132.2x27.2mm Working Humidity: 10~90% Working Temperature: -10°C ~ +45°C Storage Temperature: -20°C ~ +70°C	333\$
	Akuvox C313w SIP touch Panel 2wire	Linux SIP Indoor 1. 2-wire ports: 2 pair 2. 7" capacitive touch screen with energy saving mode 3. Reception of a HD picture from the door communicator 4. Two-way communication based on SIP v2.0 protocol 5. 48V DC connector (if not using NS-2) 6. Supports US or European electrical wall box mounting 7. front panel: plastic 8. RS485 port: Support 9. Relays out: 1 10. IO: 8 11. Installation: Wall-mounted & Desktop	222\$
	Akuvox C313S SIP touch Panel	Linux SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. POE or 12V DC Connector (if not using PoE) 5. Supports US or European electrical wall box mounting 6. front panel: plastic 7. RS485 port: Support 8. Relays out: 1 9. IO: 8 10. Installation: Wall-mounted & Desktop	160\$
	Akuvox C313N SIP touch Panel	Linux SIP Indoor 1. 7" capacitive touch screen with energy saving mode 2. Reception of a HD picture from the door communicator 3. Two-way communication based on SIP v2.0 protocol 4. Powered by PoE or external source 5. Supports US or European electrical wall box mounting 6. with one LAN port 7. I/O port not available 8. not Relay 9. front panel: plastic 10. Installation: Wall-mounted & Desktop	148\$
	Akuvox 5560	1. Wifi 2. HD audio 3. Ethernet Port: RJ45, 10/100Mbps adaptive 4. POE or 12V DC Connector (if not using PoE) 5. Installation: Wall-mounted 6. Working Humidity: 10~90%, no condensing 7. Working Temperature: -10°C~+45°C	78\$

IP Phone		VP-R49G	SIP based Android Video phone 1. 7" touch screen with 1024 x 600 resolution 2. Android 9.0 OS 3. Premium audio and video quality 4. DTMF for remote door opening 5. Camera: 2MP with privacy shutter 6. Built-in Bluetooth, USB, and Wi-Fi 7. Support 3rd-party apps 8. Support 2 Sip Account 9. RJ9 Handset 10. POE 11. Support Call Waiting, Call Forward, Call Transfer 12. Call on Hold, Mute, Auto-answer, Redial, DND 13. Local 3-Way Conference	616\$
		SP-R50P	HD Voice 2.3" 132*64 Graphical LCD with Backlight Support 3-way Conference Support PoE Fully Compatible with Asterisk, BroadSoft Platform Dimensions mm: 209 x199 x 104 Weight g: 800 Voltage: 100 ~ 240 V AC	112\$
Access Control		Akuvox A01	IP-based access control terminal that combines door controller and card reader in one device. 1. card reader: 125kHz and 13.5MHz RFID card and NFC 2. Aluminum frame, front panel Toughened Glass 3. Dimension: 86 x 86 x 33 (mm) 4. Wiegand 5. Tamper-proof Sensor 6. Relay out: 1 7. TCP/IP Communication 8. POE or 12V DC connector (if not using PoE) 9. Capacity: up to 10,000 card and 100,000 event logs 10. Water-proof & Dust-proof: IP65 11. Installation: on-wall or in-wall	207\$
		Akuvox A02	IP-based access control terminal that combines door controller and card reader in one device. 1. card reader: 125kHz and 13.5MHz RFID card and NFC 2. Aluminum frame, front panel Toughened Glass 3. Dimension: 86 x 86 x 33 (mm) 4. Wiegand 5. Tamper-proof Sensor 6. Relay out: 1 7. TCP/IP Communication 8. POE or 12V DC connector (if not using PoE) 9. Capacity: up to 20,000 card and 100,000 event logs 10. Water-proof & Dust-proof: IP65 11. Installation: on-wall or in-wall	246\$
		Akuvox A03	IP-based access control terminal combining a reader and a door controller. It offers flexible credentials, including wave-to-unlock via Bluetooth, mobile access via NFC, and RFID cards. 1. Front panel: Toughened Glass 2. Aluminum frame, front panel Toughened Glass 3. RFID card reader: 13.56MHz & 125kHz 4. Bluetooth: BLE 5.0 5. Relay out: 1 6. Inputs: 2 7. Wiegand: Support 8. Power output: 12V 600mA 9. Water-proof & Dust-proof: IP65 10. Installation: on-wall or in-wall 11. Dimension: 86 x 86 x 33 (mm) 12. Capacity: up to 20,000 card and 100,000 event logs 13. POE or 12V DC connector (if not using PoE) 14. Water-proof & Dust-proof: IP65	298\$
		Akuvox A092	Intelligent access controller housed in a stylish SGCC cabinet 1. Front panel: SGCC 2. Support up to 50,000 cards and 100,000 event logs 3. Support RS485, OSDP, and Wiegand Protocols 4. Temper-proof Sensor 5. Backlit Function icons 6. Support backup battery 7. Wiegand port: 4 8. Relays out: 2 9. Exit button input: 2 10. Installation: Wall-mounted 11. Dimension: 365 x 340 x 86 (mm) 12. POE or 12V 800mA per door for locks/strikes, readers, and input devices 13. Backup battery: Support	672\$
		Akuvox A05S + Installation kit	smart access control device with facial recognition 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3. Wiegand & RS485 Port: Support 4. NFC 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11. Installation: Wall-mounted 12. Water-proof & Dust-proof: IP65 13. Working Humidity: 10~90%, no condensing 14. Working Temperature: -20°C~+60°C	388\$ + 90\$

		Akuvox Module MD01	smart access control device with facial recognition wrist temperature measurement 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3. Wiegand & RS485 Port: Support 4. NFC 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11. Installation: Wall-mounted 12. Water-proof & Dust-proof: IP65 13. Working Humidity: 10%-90%, no condensing 14. Working Temperature: -20°C~+60°C 15. 20,000 face capacity & 20,000 card capacity	190\$
		Akuvox Module MD02	smart access control device with facial recognition with forehead temperature measurement 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3. Wiegand & RS485 Port: Support 4. NFC 5. RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11. Installation: Wall-mounted 12. Water-proof & Dust-proof: IP65 13. Working Humidity: 10%-90%, no condensing 14. Working Temperature: -20°C~+60°C 15. 20,000 face capacity & 20,000 card capacity	672\$
		A08K	Front panel: Toughened Glass Frame: Aluminum Alloy RFID card reader: 13.56MHz & 125kHz Relay out: 1 Inputs: 2 Wiegand: Support RS485: Support Speaker: 8Ω / 0.5W Tamper proof alarm: Support Ethernet port: RJ45, 10/100Mbps adaptive 12V DC connector (if not using PoE) Power output: 12V 600mA IP Level: IP65 IK Rating: IK09 Installation: Flush-mounted or Wall-mounted Dimension: 50 x 140 x 26.7 (mm) Working Humidity: 10%-90%, no condensing Working Temperature: -20°C ~ +55°C Storage Temperature: -30°C ~ +70°C	336\$
		A08S	Front panel: Toughened Glass Frame: Aluminum Alloy RFID card reader: 13.56MHz & 125kHz Relay out: 1 Inputs: 2 Wiegand: Support RS485: Support Speaker: 8Ω / 0.5W Tamper proof alarm: Support Ethernet port: RJ45, 10/100Mbps adaptive 12V DC connector (if not using PoE) Power output: 12V 600mA IP Level: IP65 IK Rating: IK09 Installation: Flush-mounted or Wall-mounted Dimension: 50 x 140 x 26.7 (mm) Working Humidity: 10%-90%, no condensing Working Temperature: -20°C ~ +55°C Storage Temperature: -30°C ~ +70°C Including PIN code, QR scanning, wave-to-unlock via Bluetooth, mobile access via NFC and RFID cards.	392\$
		Akuvox NS-2	2-Wire IP network switch 1. Support network and power supply for R20A-2 or C313W-2 through 2-wire cable; 2. Support multi-level cascade through 2-wire cable; 3. Connects up to 6 pcs of Akuvox 2-wire IP intercom devices; 4. Super long transmission distance via 2-wire cable; 5. Powered by 48VDC or 24VDC power supply unit; 6. Rail mounting installation; 7. 2-wire ports: 6 8. Status indicator: 4 9. RJ45 port: 1	235\$
		Akuvox EC-32	1. High performance 32bit CPU processor 2. Standard 10/100M TCP/IP communication 3. Big capacity flash chip, 120,000 card holders and 200,000 records 4. Each panel support 32 outputs and can connect a 5. expansion panel to reach 64 outputs 6. One RS485 port for connecting expansion panel 7. Supports emergency door release input to realize fire alarm linkage or elevator's normal usage if emergency 8. Supports 1 Wiegand reader with Wiegand 26/34 protocol 9. Support working with Akuvox intercom devices by HTTP mode	818\$